

*The Monimax 6300 offers customers the convenience of both deposit automation and bill payment. Banks benefit, too, because this kiosk model requires less initial investment and on-going maintenance costs than a full-function ATM.*

## Features

### **Supports Check Deposit and Bill Payment**

Featuring a high-end check-and-cash scanning unit, the Monimax 6300 offers auto alignment, dual-side scans, endorsement printing and MICR recognition.

### **Multi-functional and Secure**

The Monimax 6300 is an ideal solution for both in- and out-of-branch locations. It satisfies demanding security standards such as UL 291 Level 1 safety, Encrypt Pin Pad, Triple-DES and Check 21 regulation compliance.

### **Easy Installation and Maintenance**

Thanks to its modular architecture, the Monimax 6300 requires only simple installation and maintenance. It is also highly reliable. With maximum uptime and low operating costs, you can enjoy increased return on your investment.



***Superior quality, security and value.***

***Only with Nautilus Hyosung.***

*Now offering the most complete line of financial and retail ATMs.*

### **Dependable Customer Service**

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.



# MONIMAX 6300

## System Control

- Intel® Pentium IV® processor
- Microsoft® Windows XP® platform
- NDC+, DDC912, User Application

## Customer Display

- 15" color TFT LCD
- Optional**
- Privacy filter

## Communication

- TCP/IP (SSL configurable)
- Optional**
- Dial-up, Wireless, X.25

## Input Type

- 4 x 2 function keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant
- Optional**
- Touch screen

## Card Handling

- Dip-type card reader
- Optional**
- IC card reader  
EMV Level 1, 2 compliant
- Anti-skimming

## Cash Acceptor

- 2,000 notes capacity
- Bulk-note feed module

## Check Acceptor

- 1,000 notes capacity
- Single check acceptor
- Dual side scannig
- MICR reader

## Printers

- 3.1" graphical thermal receipt printer
- 3,500 transactions
- Electronic journal

## Security

- UL291 business hour safe
- Mechanical combination lock
- Optional**
- Electronic safe lock
- KABA Mas Cencon safe lock
- Security camera

## Miscellaneous

- Lead-through indicator
- Electronic journal
- Optional**
- Heater
- Vacuum Fluorescent Display (VFD)

## Power Supply

- AC 110–230V, 50–60 Hz
- Back-up battery

## Operating Environment

- Temperature: 28°F–104°F
- Humidity: 25%–85%

## Dimension and Weight

- Height: 61.1" (1,552 mm)
- Width: 18.1" (460 mm)
- Depth: 30.7" (780 mm)
- Weight: 705 lbs (320 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accomodate the changes in technology.

**Secure**  
Communications  
**Dial-up or**  
**Built-in TCP/IP**  
**and SSL**



**Nautilus**  
HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.