

This walk-up, through-the-wall ATM is designed for high-traffic areas with the capacity to hold up to 6,000 notes. Plus, it offers true flexibility for future expansion.

Features

Powerful Transaction Support

With the Microsoft Windows XP Platform and an Intel Pentium Processor, the Monimax 7000T guarantees support for both larger and faster transactions.

High Level of Scalability.

Designed to support multi-vendor solutions, this ATM can easily support additional financial services, including an optional envelope depository.

Reliability

The Monimax 7000T satisfies demanding performance standards such as UL 291Level 1 and PCI-certified encrypting PIN pad.

***Superior quality, security and value.
Only with Nautilus Hyosung.***



The Monimax 7000T offers a customer-centric interface with the power to grow with your business.

Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

MONIMAX 7000T

System Control

- Microsoft® Windows XP® platform
- Intel® Pentium®-IV processor
- Application NDC+, VISA2

Customer Display

- 10.4" TFT LCD
- Sunlight viewable

Communication

- NDC+ : TCP/IP
- VISA2 : TCP/IP (SSL configurable)
Dial-up

Input Type

- 4 x 2 function keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

Supervisor Operation

- 5.7" Mono display
- 4 x 4 numeric keys
- 4 x 2 function keys

Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

Cash Dispensing

- 2,000-note cassettes
- Optional cassettes (up to three)

Depository

Optional

- Envelope depository

Printers

- 3.1" graphical thermal receipt printer

Security

- UL291 Level 1 safe
- Electronic safe lock
- Optional KABA Mas Cencon safe lock

Miscellaneous

- Lead-through indicator
- Illuminated signage

Optional

- Heater
- Electronic journal

Power Supply

- AC 110–230V, 50–60 Hz

Operating Environment

- Temperature: -32°F–104°F
- Humidity: 25%–85%

Dimension and Weight

- Height: 61.2" (1,548 mm)
- Width: 32.6" (830 mm)
- Depth: 38.6" (982 mm)
- Weight: 1,440 lbs (650 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



 NAUTILUS HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.