

The Monimax 7600T is the ideal choice for handling high-volume transactions with the capacity to hold up to 12,000 notes. It also offers the newest technology that accepts bundle-note or bundle-check deposits.

Features

Powerful Transaction Support

With the Microsoft Windows XP platform and an Intel Pentium IV Processor, the Monimax 7600T guarantees support for both larger and faster transactions, including envelope-free bundle check and bundle cash deposits.

Fully Upgradeable

The 7600T lets you deploy deposit automation upgrades when your institution is ready.

Reliability

The Monimax 7600T satisfies demanding performance standards such as UL 291Level 1 and PCI-certified encrypting PIN pad.

Deposit automation features save you money.

By eliminating the need for envelopes, you can reduce your printing costs. Plus, you can save tons of paper over time, giving you the power to build your image as an earth friendly company.

Superior quality, security and value.

Only with Nautilus Hyosung.



Deposit automation saves you money by reducing your printing costs. Plus, you can save tons of paper over time, giving you the power to build your image as an earth friendly company.



The Monimax 7600T offers the latest deposit automation technology. The upgradeable design allows it to grow with your business.

MONIMAX 7600T

System Control

- Microsoft® Windows XP® platform
- Intel® Pentium®-IV processor
- NDC+, User Application

Customer Display

- 15" color TFT LCD

Optional

- Privacy filter (standard)
- Sunlight readable (standard)

Communication

- TCP/IP

Input Type

- PCI EPP (Encrypting PIN pad)
- ADA compliant

Supervisor Operation

- 15" TFT color LCD, touch screen

Card Handling

- Dip-type card reader

Optional

- IC card reader EMV Level 1, 2 compliant
- Anti-skimming
- Motor-driven card reader

Cash Dispensing

- 3,000-notes cassette
Up to four cassettes
- Bundle retraction
- Automatic shutter

Depository

- Bundle check scanner and acceptor
- Bundle note acceptor

Optional

- Envelope depository

Printers

- 3.1" graphical thermal receipt printer
- 5,000 transaction receipt printer
- Electronic journal

Security

- UL291 Level 1 safe

Optional

- Electronic safe lock (standard)
- Optional KABA Mas Cencon safe lock
- Optional security camera (standard)

Miscellaneous

- Lead-through indicator
- Heater (standard)

Power Supply

- AC 110–240V, 50–60 Hz
- Back-up battery

Operating Environment

- Temperature: -31°F–104°F
- Humidity: 25%–85%

Dimension and Weight

- Height: 69.3" (1,760 mm)
- Width: 32.7" (831 mm)
- Depth: 40.6" (1,032 mm)
- Weight: 1,977.5 lbs (897 kg)



 NAUTILUS HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.